

**RCR12 Series**

Features	Benefits
<b>Surpassed rugged industry standards</b>	All Land Pride cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
<b>Tractor Horsepower range</b>	18 - 60 horsepower
<b>3 Year gearbox warranty</b>	Shows our confidence in the gearbox integrity.
<b>Cat. 3 driveline with shear-bolt</b>	Shear bolt offers maximum driveline protection.
<b>Cat. 3 driveline with 2-plate slip-clutch</b>	Slip-clutch driveline offers convenience for continual work.
<b>Floating top link</b>	Provides for easy hook-up. Permits deck to follow the terrain for an even cut. Two hole position to allow greater lift leverage for smaller tractors.
<b>Round back design</b>	Helps discharge grass better than enclosed or partially enclosed cutters.
<b>1 1/4" - 10" Cutting Height</b>	Cutting height for wide range of cutting conditions.
<b>Skid shoes (Accessory) RCR1260 &amp; RCR1272 only</b>	Provides sidewall reinforcement and helps protect bottom of sidewall.
<b>1/2" x 3" Heat-treated free swinging blades</b>	Free swinging protects from obstructions. Heat-treated offers longer life.
<b>Splined blade bar hub</b>	Allows for tight positive fit of stump jumper and blade bar to gearbox output shaft.
<b>10 Gauge stump jumper</b>	Allows cutter to slide over obstructions protecting the gearbox output shaft.
<b>High blade tip speed</b>	Ensures clean cut.
<b>Laminated tailwheel</b>	Laminated material is long lasting in rough conditions and can't go flat.
<b>Heavy-duty spindle on tailwheel</b>	1 1/4" spindle gives the strength to protect tailwheel assembly.
<b>Rubber guarding</b>	Protect against flying debris.
<b>Metal Guarding</b>	Protects against flying debris.