



## RCR2660 & RCR2672 Models

Specifications & Capacities		
	RCR2660	RCR2672
Machine Weight (with Chain Guards)	1,002#	1,046#
Hitch	Category I or II Quick Hitch Compatible with Floating Top Link, Quick Hitch Ready	
Cutting Width	60" (152 cm)	72" (183 cm)
Overall Width	67" (170 cm)	79" (201 cm)
Overall Length (Including Tailwheel)	110 1/2" (281 cm)	123" (313 cm)
Deck Height	9 1/8" (23 cm) Bottom of Deck to Bottom of Skid Shoe	
Cutting Height	2" - 12" (5-31 cm)	
Cutting Capacity	3" (8 cm)	
Recommended Tractor horsepower	35-130 (26-97 kW) maximum	
Power Take-Off Speed	540 rpm	
Gearbox	540 rpm power take-off Driven Gearbox 1:1.46 Speed-Up Beveled Gears Cast Iron Housing	
Gearbox Lubrication Capacity & Type	7 pints (3.3 L) of 80-90W EP oil	
Gearbox Input/ Output Shaft Size	Input Shaft = 1 3/8" - 6 Spline Output Shaft = 2" Dia.	
Deck Construction	All welded construction	
Deck Material Thickness	10 Gauge (3.4 mm)	
Side Panel Thickness	1/4" (6 mm)	
Skids	Replaceable	
Round Pan Stump Jumper	3/16" x 24" (5 mm x 61 cm)	3/16" x 30 1/2" (5 mm x 78 cm)
Blades (2)	1/2" x 4" x 25" Heat Treated Alloy Steel Free-Swinging High Lift	1/2" x 4" x 29" Heat Treated Alloy Steel Free-Swinging High Lift
Blade Bolt	Keyed with harden flat washer and locknut	
Blade Tip Speed	12,384 fpm @ 788 rpm (63 mps @ 788 rpm))	14,861 fpm @ 788rpm (76 mps @ 788 rpm)
Driveline	ASAE Category 4	
Driveline Protection	4 Plate Slip Clutch	
Tailwheel Mount Assembly	Welded arm and Caster Fork	
Tailwheel	4.00 x 8 x 15 Laminated Tire with cast iron hub and tapered roller bearings	
Front Guard	Optional: Chain Guard Available through Parts Department: Rubber Guard	
Rear Guard	Optional: Chain Guard	

