

RCF2784 & RCR2684

Features	Benefits
Surpassed rugged industry standards	All Land Pride cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
5 Year gearbox warranty	A rugged heavy built gearbox capable of handling heavy cutting applications. Shows Land Pride's confidence in gearbox integrity.
Gearbox seal protection	Gearbox bottom seal protection for longer bearing life.
130 Horsepower gearbox	A rugged heavy built gearbox capable of handling heavy cutting applications.
Cat. 4 driveline with 4-plate slip-clutch	Excellent gearbox protection with the slip-clutch slipping when encountering obstruction in blade path. Standard slip-clutch offers convenience over shear-bolts.
Cat. II or III hitch with floating top link	Permits deck to follow the terrain for an even cut.
Quick Hitch Capability	Quick Hitch provides for fast hook-up.
Lower clevis type 3-point hitch	Allows for ease of hook-up to tractor. Also adds additional strength allowing for an even pull from the tractor's lower arms, vs. pulling on a single pin design.
84" Cutting width	Wide cutting width, Reduces cutting time in the field.
Heavy 10 gauge deck & 1/4" side skirt construction	10 gauge deck can withstand more abuse than lighter gauge decks and 1/4" side skirts provide excellent reinforcement and also protect sides from debris being thrown against them from the blades.
Box tubing deck supports	Makes for a stronger rigid deck.
Fully welded deck	Robotic welded. Adds additional strength and deck integrity.
Extended cutter front	For increased material flow and added protection.
Round back design	Helps discharge grass better than enclosed or partially enclosed cutters. Also allows for more efficient handling.
Deck Height 10 1/8" (RCF2784) 9 7/8" (RCR2684)	Allows cutter to handle heavy cutting conditions.
1 1/2" to 12" Cutting height	Provides for a wide range of cutting conditions.
High cutting capacity	Can cut brushy areas with saplings up to 3".
Full length skids with replaceable shoes	Full length skids protect side plate structure, replaceable shoes for convenience.
1/2" x 4" Heat-treated free swinging blades	Free swinging protects from obstructions. Heat-treated offers longer life.
Splined blade bar	Allows for tight positive fit of stump jumper and blade bar to gearbox output shaft.
Oval stump jumper	Standard stump jumper aids in sliding over obstructions such as stumps, rocks and debris, which also helps protect gearbox output shaft.
High blade tip speed	Ensures clean cut. (14,369 fpm)
Available with single or dual tailwheel	Dual tailwheels offer greater stability in uneven terrain.
15" Laminated tailwheel	Laminated material is long lasting in rough conditions. Can't go flat.
1 1/2" Heavy-duty spindle on tailwheel(s)	Tailwheels take a beating, spindle gives the strength to protect tailwheel assembly.
Optional front guarding	Protect against flying debris. Customer can choose to include single chain, double chain or rubber guarding.
Optional rear guarding	Protect against flying debris. Customer can choose to include single chain or double chain.
Standard rear metal band	Protects against flying debris. Acts as a baffle o help mulch cuttings into smaller pieces.