

RCF3096 & RCF(M)3010 Models

Features	Benefits
Surpassed rugged industry standards	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures.
540 or 1000 rpm	Fits wider variety of tractors.
High gearbox hp rating	Gearboxes are built rugged. See Specifications for actual Gearbox hp ratings.
5 Yr. limited gearbox warranty	Shows our confidence in the gearbox integrity.
3 Gearboxes	Allows equal torque to be spread to left and right gearbox.
Splined rubber flex-couplers between the center and outboard gearboxes	Protects the driveline and gearboxes from hard objects in the blade path.
Pull-Type constant velocity driveline option	Constant velocity driveline reduces chatter and extends life of U-joint during turns.
Slip-clutch protection on main driveline	Slip-clutch is more convenient than shear-bolt, protects gearbox against sudden impact.
8'- Cat. 1 & 2 or 10'- Cat. 2 & 3 3-Point & Semi-mount hitches or pull-type hitch	Fits a wide range of tractors. Semi-mount and Pull-type fit older tractors without a top link and smaller tractors without enough lift capacity.
10 Gauge deck, fully welded	Fully welded deck adds rigidity.
1/4" Thick sidewalls	Protects sidewalls from thrown objects.
Round back design	Allows for cleaner and efficient discharge of material, helps eliminate damage to rear corners by not sticking out.
Pull-type w/dual leveling rods	Dual leveling rods eliminate deck twisting when going over uneven terrain.
Chain or rubber guard option	Reduces flying debris.
Full length skids with replaceable shoes	Adds reinforcement to side panels. Replaceable shoes allow for change before wearing through to weld-on piece.
Splined blade hub	Splined blade hub offers tight non-slipping attachment to output shaft.
3/16" Round stump jumper	Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft.
1" x 4" Blade bar	Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft.
1/2" x 4" Heat-treated blades	Heat-treated blades last longer than non-heat-treated blades.
2 1/2" Diameter cutting capacity	Aids in cutting brush.
High blade tip speed	Means cleaner cutting. See Specifications for actual blade tip speeds.
Laminated tires	Laminated tires can handle almost any condition and don't go flat.
Quick Hitch adaptable	3-Point and semi-mount are Quick Hitch adaptable.