

RCF(M)3696 & RCF(M)3610 Models

All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures. Fits wider variety of tractors.	Features	Benefits
High gearbox hp rating Gearboxes are built rugged. See Specifications for actual Gearbox hp ratings.		
Seri-Numited gearbox warranty 3 Gearboxes Allows equal torque to be spread to left and right gearbox. Splined rubber flex-couplers between the center and outboard gearboxes Pull-Type constant velocity driveline and gearboxes from hard objects in the blade path. Slip-clutch protection on main driveline 8'- Cat. 1 & 2 or 10'- Cat. 2 & 3 3-point & semi-mount hitches or pull-type hitch 10 Gauge deck, fully welded Fully welded deck adds rigidity. Full-Type w/dual leveling rods Chain or rubber guard option Pull-Type w/dual leveling rods Pull-Type w/dual leveling rods Pull seving shots Adds reinforcement to side panels. Replaceable shoes allow for change before wearing with replaceable shoes Splined blade hub Splined blade hub offers tight non-slipping attachment to output shaft. 1" x 5" Blade bar Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft. 1/2" x 4" Heat-treated blades The pull-treated blades Weans cleaner cutting. See Specifications for actual blade tip speeds. Laminated tires Laminated tires can handle almost any condition and don't go flat.	540 or 1000 rpm	Fits wider variety of tractors.
Allows equal torque to be spread to left and right gearbox. Splined rubber flex-couplers between the center and outboard gearboxes Pull-Type constant velocity driveline and gearboxes from hard objects in the blade path. Constant velocity driveline reduces chatter and extends life of U-joint during turns. Slip-clutch protection on main driveline Slip-clutch is more convenient than shear-bolt, protects gearbox against sudden impact. Semi-Mount and Pull-Type fit older tractors without a top link and smaller tractors without enough lift capacity. Gauge deck, fully welded Fully welded deck adds rigidity. Protects sidewalls Protects sidewalls from thrown objects. Round back design Allows for cleaner and efficient discharge of material, helps eliminate damage to rear corners by not sticking out. Pull-Type w/dual leveling rods Dual leveling rods eliminate deck twisting when going over uneven terrain. Chain or rubber guard option Reduces flying debris. Full length skids with replaceable shoes Splined blade hub Splined blade hub offers tight non-slipping attachment to output shaft. Standard stump jumper Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft. 1" x 5" Blade bar Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft. 1/2" x 4" Heat-treated blades "Heat-treated blades last longer than non-heat-treated blades. "Diameter cutting capacity Alds in cutting brush. High blade tip speed Laminated tires Laminated tires can handle almost any condition and don't go flat.	High gearbox hp rating	Gearboxes are built rugged. See Specifications for actual Gearbox hp ratings.
Splined rubber flex-couplers between the center and outboard gearboxes Pull-Type constant velocity driveline roduces chatter and extends life of U-joint during turns. Slip-clutch protection on main driveline 8'- Cat. 1 & 2 or 10'- Cat. 2 & 3 3-point & semi-mount hitches or pull-type hitch 10 Gauge deck, fully welded Fully welded deck adds rigidity. 11/4" Thick sidewalls Protects sidewalls from thrown objects. Round back design Allows for cleaner and efficient discharge of material, helps eliminate damage to rear corners by not sticking out. Pull-Type w/dual leveling rods Chain or rubber guard option Full length skids with replaceable shoes Splined blade hub Splined blade hub Splined blade hub Standard stump jumper Aids reinforcement to side panels. Replaceable shoes allow for change before wearing through to weld-on piece. Splined blade hub Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft. 1" x 5" Blade bar Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft. 1/2" x 4" Heat-treated blades Heat-treated blades last longer than non-heat-treated blade itp speed Laminated tires Laminated tires can handle almost any condition and don't go flat.	5 Yr. limited gearbox warranty	Shows our confidence in the gearbox integrity.
Protects the driveline and gearboxes from hard objects in the blade path. Pull-Type constant velocity driveline reduces chatter and extends life of U-joint during turns. Slip-clutch protection on main driveline 8'- Cat. 1 & 2 or 10'- Cat. 2 & 3 3-point & semi-mount hitches or pull-type hitch 10 Gauge deck, fully welded Fully welded deck adds rigidity. 1/4" Thick sidewalls Protects sidewalls from thrown objects. Round back design Allows for cleaner and efficient discharge of material, helps eliminate damage to rear corners by not sticking out. Pull-Type widual leveling rods Dual leveling rods eliminate deck twisting when going over uneven terrain. Chain or rubber guard option Reduces flying debris. Full length skids with replaceable shoes Plined blade hub Splined blade hub Splined blade hub Splined blade hub Gress through to weld-on piece. Splined blade hub Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft. 1" x 5" Blade bar Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft. 1/2" x 4" Heat-treated blades Heat-treated blades Heat-treated blades last longer than non-heat-treated blade tip speed Means cleaner cutting. See Specifications for actual blade tip speeds. Laminated tires Laminated tires can handle almost any condition and don't go flat.	3 Gearboxes	Allows equal torque to be spread to left and right gearbox.
Slip-clutch protection on main driveline Slip-clutch protection on main driveline Slip-clutch is more convenient than shear-bolt, protects gearbox against sudden impact. Slip-clutch is more convenient than shear-bolt, protects gearbox against sudden impact. Fits a wide range of tractors. Semi-Mount and Pull-Type fit older tractors without a top link and smaller tractors without enough lift capacity. In Gauge deck, fully welded Fully welded deck adds rigidity. Protects sidewalls from thrown objects. Round back design Allows for cleaner and efficient discharge of material, helps eliminate damage to rear corners by not sticking out. Pull-Type w/dual leveling rods Dual leveling rods eliminate deck twisting when going over uneven terrain. Chain or rubber guard option Reduces flying debris. Full length skids with replaceable shoes Splined blade hub Splined blade hub offers tight non-slipping attachment to output shaft. 3/16" Round stump jumper Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft. 1" x 5" Blade bar Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft. Heat-treated blades Beat-treated blades last longer than non-heat-treated blades. "Beat dear cutting capacity Aids in cutting brush. High blade tip speed Laminated tires can handle almost any condition and don't go flat.	between the center and	Protects the driveline and gearboxes from hard objects in the blade path.
Sip-clutch is more convenient train shear-both, protects gearbox against studien impact. 8'- Cat. 1 & 2 or 10'- Cat. 2 & 3 3-point & semi-mount hitches or pull-type hitch 10 Gauge deck, fully welded Fully welded deck adds rigidity. Full-Type w/dual leveling rods Dual leveling rods eliminate deck twisting when going over uneven terrain. Reduces flying debris. Full length skids Adds reinforcement to side panels. Replaceable shoes allow for change before wearing through to weld-on piece. Splined blade hub Splined blade hub Splined blade hub offers tight non-slipping attachment to output shaft. Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft. The x 5" Blade bar Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft. Heavy-duty blades last longer than non-heat-treated blades. Heat-treated blades last longer than non-heat-treated blade tip speeds. Laminated tires Laminated tires can handle almost any condition and don't go flat.		Constant velocity driveline reduces chatter and extends life of U-joint during turns.
3-point & semi-mount hitches or pull-type hitchSemi-Mount and Pull-Type fit older tractors without a top link and smaller tractors without enough lift capacity.10 Gauge deck, fully weldedFully welded deck adds rigidity.1/4" Thick sidewallsProtects sidewalls from thrown objects.Round back designAllows for cleaner and efficient discharge of material, helps eliminate damage to rear corners by not sticking out.Pull-Type w/dual leveling rodsDual leveling rods eliminate deck twisting when going over uneven terrain.Chain or rubber guard optionReduces flying debris.Full length skids with replaceable shoesAdds reinforcement to side panels. Replaceable shoes allow for change before wearing through to weld-on piece.Splined blade hubSplined blade hub offers tight non-slipping attachment to output shaft.3/16" Round stump jumperStandard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft.1" x 5" Blade barHeavy-duty blade bar adds support to stump jumper as well as gearbox output shaft.1/2" x 4" Heat-treated bladesHeat-treated blades last longer than non-heat-treated blades.3" Diameter cutting capacityAids in cutting brush.High blade tip speedMeans cleaner cutting. See Specifications for actual blade tip speeds.Laminated tiresLaminated tires can handle almost any condition and don't go flat.		Slip-clutch is more convenient than shear-bolt, protects gearbox against sudden impact.
1/4" Thick sidewalls Protects sidewalls from thrown objects. Allows for cleaner and efficient discharge of material, helps eliminate damage to rear corners by not sticking out. Pull-Type w/dual leveling rods Dual leveling rods eliminate deck twisting when going over uneven terrain. Chain or rubber guard option Reduces flying debris. Full length skids with replaceable shoes Adds reinforcement to side panels. Replaceable shoes allow for change before wearing through to weld-on piece. Splined blade hub Splined blade hub offers tight non-slipping attachment to output shaft. 3/16" Round stump jumper Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft. 1" x 5" Blade bar Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft. 1/2" x 4" Heat-treated blades Heat-treated blades last longer than non-heat-treated blades. 3" Diameter cutting capacity Aids in cutting brush. High blade tip speed Means cleaner cutting. See Specifications for actual blade tip speeds. Laminated tires Laminated tires can handle almost any condition and don't go flat.	3-point & semi-mount hitches	Semi-Mount and Pull-Type fit older tractors without a top link and smaller tractors without
Allows for cleaner and efficient discharge of material, helps eliminate damage to rear corners by not sticking out. Pull-Type w/dual leveling rods Dual leveling rods eliminate deck twisting when going over uneven terrain. Chain or rubber guard option Reduces flying debris. Full length skids Adds reinforcement to side panels. Replaceable shoes allow for change before wearing through to weld-on piece. Splined blade hub Splined blade hub offers tight non-slipping attachment to output shaft. 3/16" Round stump jumper Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft. 1" x 5" Blade bar Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft. 1/2" x 4" Heat-treated blades Heat-treated blades last longer than non-heat-treated blades. 3" Diameter cutting capacity Aids in cutting brush. High blade tip speed Means cleaner cutting. See Specifications for actual blade tip speeds. Laminated tires can handle almost any condition and don't go flat.	10 Gauge deck, fully welded	Fully welded deck adds rigidity.
corners by not sticking out. Pull-Type w/dual leveling rods Dual leveling rods eliminate deck twisting when going over uneven terrain. Chain or rubber guard option Full length skids with replaceable shoes Adds reinforcement to side panels. Replaceable shoes allow for change before wearing through to weld-on piece. Splined blade hub Splined blade hub offers tight non-slipping attachment to output shaft. 3/16" Round stump jumper Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft. 1" x 5" Blade bar Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft. 1/2" x 4" Heat-treated blades Heat-treated blades last longer than non-heat-treated blades. 3" Diameter cutting capacity High blade tip speed Means cleaner cutting. See Specifications for actual blade tip speeds. Laminated tires Laminated tires can handle almost any condition and don't go flat.	1/4" Thick sidewalls	Protects sidewalls from thrown objects.
Chain or rubber guard option Reduces flying debris. Full length skids with replaceable shoes Splined blade hub Splined blade hub offers tight non-slipping attachment to output shaft. 3/16" Round stump jumper Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft. 1" x 5" Blade bar Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft. 1/2" x 4" Heat-treated blades Heat-treated blades last longer than non-heat-treated blades. 3" Diameter cutting capacity High blade tip speed Means cleaner cutting. See Specifications for actual blade tip speeds. Laminated tires Laminated tires can handle almost any condition and don't go flat.	Round back design	
Full length skids with replaceable shoes Splined blade hub Splined blade hub offers tight non-slipping attachment to output shaft. 3/16" Round stump jumper Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft. 1" x 5" Blade bar Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft. 1/2" x 4" Heat-treated blades Heat-treated blades last longer than non-heat-treated blades. 3" Diameter cutting capacity High blade tip speed Means cleaner cutting. See Specifications for actual blade tip speeds. Laminated tires Laminated tires can handle almost any condition and don't go flat.	Pull-Type w/dual leveling rods	Dual leveling rods eliminate deck twisting when going over uneven terrain.
through to weld-on piece. Splined blade hub Splined blade hub offers tight non-slipping attachment to output shaft. 3/16" Round stump jumper Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft. 1" x 5" Blade bar Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft. 1/2" x 4" Heat-treated blades Heat-treated blades last longer than non-heat-treated blades. 3" Diameter cutting capacity High blade tip speed Means cleaner cutting. See Specifications for actual blade tip speeds. Laminated tires Laminated tires can handle almost any condition and don't go flat.	Chain or rubber guard option	Reduces flying debris.
3/16" Round stump jumper Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft. 1" x 5" Blade bar Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft. 1/2" x 4" Heat-treated blades Heat-treated blades last longer than non-heat-treated blades. 3" Diameter cutting capacity Aids in cutting brush. High blade tip speed Means cleaner cutting. See Specifications for actual blade tip speeds. Laminated tires Laminated tires can handle almost any condition and don't go flat.		
output shaft. 1" x 5" Blade bar Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft. 1/2" x 4" Heat-treated blades Heat-treated blades last longer than non-heat-treated blades. 3" Diameter cutting capacity Aids in cutting brush. High blade tip speed Means cleaner cutting. See Specifications for actual blade tip speeds. Laminated tires Laminated tires can handle almost any condition and don't go flat.	Splined blade hub	Splined blade hub offers tight non-slipping attachment to output shaft.
1/2" x 4" Heat-treated blades Heat-treated blades last longer than non-heat-treated blades. 3" Diameter cutting capacity Aids in cutting brush. High blade tip speed Means cleaner cutting. See Specifications for actual blade tip speeds. Laminated tires Laminated tires can handle almost any condition and don't go flat.	3/16" Round stump jumper	
3" Diameter cutting capacity Aids in cutting brush. High blade tip speed Means cleaner cutting. See Specifications for actual blade tip speeds. Laminated tires Laminated tires can handle almost any condition and don't go flat.	1" x 5" Blade bar	Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft.
High blade tip speed Means cleaner cutting. See Specifications for actual blade tip speeds. Laminated tires Laminated tires can handle almost any condition and don't go flat.	1/2" x 4" Heat-treated blades	Heat-treated blades last longer than non-heat-treated blades.
Laminated tires	3" Diameter cutting capacity	Aids in cutting brush.
·	High blade tip speed	Means cleaner cutting. See Specifications for actual blade tip speeds.
Quick Hitch adaptable 3-Point and semi-mount are Quick Hitch adaptable.	Laminated tires	Laminated tires can handle almost any condition and don't go flat.
	Quick Hitch adaptable	3-Point and semi-mount are Quick Hitch adaptable.