

# RCR15 SERIES SINGLE SPINDLE ROTARY CUTTERS

HP REQUIRED  
20-60 HP

CUTTING CAPACITY  
2"

HITCH  
Cat. 1 & 1 Ltd.



CUTTERS

## Efficient handling and dispersing of material.

For small acreage owners looking for a heavier cutter, Land Pride offers the RCR1548. It features a 2" cutting capacity, a high blade tip speed, and larger gearbox than the RCR12. Ideal for maintenance of lanes, pastures, and other rough-cut areas.



Round back design helps discharge grass better than enclosed or partially enclosed cutters. The fully welded deck adds additional strength.

**5 YEAR LIMITED GEARBOX WARRANTY**



Two position floating top link offers greater lifting leverage for subcompact tractors, and allows deck to hug the terrain.



10 Gauge stump jumper allows cutter to slide over obstructions protecting the gearbox output shaft.



Heavy-duty 1-1/4" spindle on the tailwheel gives strength to protect the tailwheel assembly.

	RCR1548
<b>Horsepower</b>	20-60 HP
<b>Hitch</b>	Cat. 1 & Cat. 1 Limited
<b>Working Width (cm)</b>	47-1/2" (121)
<b>Overall Width</b>	53-1/2"
<b>Overall Length</b>	91-3/4"
<b>Weight - lb (kg)</b>	424 (192)
<b>Cutting Height</b>	1-3/4" - 11-1/2"
<b>Cutting Capacity</b>	2" Diameter
<b>Deck Thickness</b>	12 Gauge
<b>Deck Height</b>	7-1/4"
<b>Safety Guards</b>	Rubber Front and Rear
<b>Skids</b>	1/4" x 2" Weld On
<b>Blades</b>	1/2" x 3" Heat Treated Alloy Steel Free Swinging Blades
<b>Blade Tip Speed</b>	13,090 fpm
<b>Dishpan</b>	Round 10 Gauge x 24" Diameter, Dish Shaped
<b>Gearbox Rating<sup>^</sup></b>	65 HP
<b>Gearbox</b>	540 RPM PTO Driven Gearbox Cast Iron Housing
<b>Driveline</b>	Cat. 3, Standard - 1/2" Shear Bolt Protection Optional - Bolt 2 Plate Slip Clutch
<b>Tailwheel</b>	4" x 16" Molded Rubber Tire
<b>Colors</b>	



\*See dealer for complete warranty information. ^Based on field performance.