

RCR18 SERIES SINGLE SPINDLE ROTARY CUTTERS

HP REQUIRED
20-90 HP

CUTTING CAPACITY
2"

HITCH
Cat. 1 & 2

CUTTERS



Ideal for cleaning around the farm, the pond, or empty lots in the city.

- Floating 3-Point allows deck to follow the terrain
- Fully-welded deck adds additional strength
- High blade tip speed ensures clean cut
- Single or dual tailwheel on 84"
- Heavy-duty tailwheel spindle
- All-welded formed channels front to rear add superior strength
- Lower clevises for easy hookup



5 YEAR
LIMITED GEARBOX
WARRANTY*



Protect against flying debris with rubber or chain guards on the front and metal band on the rear.



Floating 3-Point allows for easy hook-up and permits deck to follow the terrain.



10 Gauge stump jumper with 1" thick blade bar slides over stumps, rocks and debris.

	RCR1860	RCR1872	RCR1884
Horsepower	20-65 HP		45-90 HP
Hitch	Cat. 1		Cat. 1 & 2
Working Width (cm)	57" (145)	69" (173)	84" (213)
Overall Width	65"	77"	89"
Overall Length	99-3/8"	110"	135"
Weight - lb (kg)	599 (272)	737 (334)	851 (386)
Cutting Height	1-1/2" - 13"	1-1/2" - 11-1/2"	2" - 11"
Cutting Capacity	2" Diameter		
Deck Thickness	10 Gauge		
Deck Height	7-1/2"	9"	9-1/8"
Safety Guards	Rubber or Chain, Rear Metal Band - Standard		
Skids	1/4" x 2" Weld On		
Blades	Heat Treated Alloy Steel Free Swinging Blades		
	1/2" x 3"		1/2" x 4"
Blade Tip Speed	16,363 fpm	14,853 fpm	17,113 fpm
Dishpan	Round 10 Gauge x 24" Diameter, Dish Shaped	Oval 10 Gauge, Dish Shaped	
Gearbox Rating[^]	65 HP	130 HP	
Gearbox	540 RPM, PTO Driven Gearbox		
Driveline	Standard - 1/2" Shear Bolt Protection Optional - Bolt 2 Plate Slip Clutch		
	Cat. 3		Cat. 4
Tailwheel	4" x 16" Solid Rubber Tire, Cast Iron Hub		4" x 8" x 15" Laminated Tire or Fual Laminated Optional, Cast Iron Hub
Colors			

QUICK HITCH
SYSTEM