RCR25 SERIES DUAL SPINDLE

ROTARY CUTTERS









A perfect fit for any size farm.

The RCR25 Series is well-suited for medium sized chores and is designed for performance in pastures, set aside acres, roadsides, and routine farm maintenance.

Pull-Type: The Pull-Type model features two leveling rods that connect the rear axle to the front tongue. This enables the deck to stay level over uneven ground conditions. The height controlling axle cylinder is attached to two deck springs that help cushion the cutter in rough terrain. A narrow tongue on Pull-Type allows for tight turns.

3-Point: The 3-Point unit utilizes two castering laminated tailwheels for smooth, trouble-free performance. The easy to attach clevis hitch is designed to fit Cat. 1 or 2 tractors on the 96" model, and Cat. 2 or 3 tractors on the 10' model.

Slip clutch and impact absorbing cross shafts to outer gearboxes

• Constant Velocity U-Joint option on 10' Pull-Type

Slip clutch protection on main driveline

Fully welded 10 Gauge deck

· Round back design

Chain or rubber shield option

Replaceable skid shoes

• 1" x 4" Blade bar



		RCR2596	RCR2510
	Horsepower	Pull: 40-110 HP 3-Pt: 50-110 HP	Pull: 50-110 HP 3-Pt: 60-110 HP
	Hitch	Cat. 1 & 2	Cat. 2 & 3
W	orking Width (cm)	7'10" (239)	9'10" (300)
	Overall Width	8'3-3/4"	10'3-1/2"
	Overall Length	Lift - 8'10", Pull - 11'8-3/4"	Lift - 9'4", Pull - 12'6"
	Weight - Ib (kg)	3-Pt: 1,380 (625) Pull: 1,665 (755)	3-Pt: 1,750 (793) Pull: 2,035 (923)
Deck Thickness		10 Gauge	
	Deck Height	9-5/8"	
	*Safety Guards (choose)	Front: Rubber or Chain Rear: Rubber or Chain	
Skids		Replaceable	
	Gearbox Rating^	210 HP Splitter 90 HP Outboard	
Gearbox		540 rpm, Cast Iron Housing, Beveled Gears	
	Cutting Height	2" - 12"	2" - 10-1/2"
	Cutting Capacity	1-1/2" Diameter	
	Blades	1/2" x 4" Heat Treated, Free-Swinging Suction Blades	
	Blade Tip Speed	14,592 fpm	17,749 fpm
	Dishpan	3/16", Round, Dish Shaped	
8/	Driveline	Plate Slip Clutch	
Tailwheel p		Lift-Type: 2 Each, 4" x 8" x 15-1/4" Laminated Pull-Type: 2 Each, 6" x 9" x 21" Laminated or 24" Aircraft Tires	
Colors			



