

RCR26 SERIES SINGLE SPINDLE ROTARY CUTTERS

HP REQUIRED
35-130 HP

CUTTING CAPACITY
3"

HITCH
Cat. 1, 2 & 3

CUTTERS



Roundback design allows for more efficient handling and dispersing of material.

Land Pride's 26 Series Rotary Cutters are a good choice for use around the farm, keeping the horse pastures under control, maintaining lanes, or clearing rough areas. The 3" cutting capacity also allows it to be the choice of many municipalities from parks to easement control applications.

- Full length skids with replaceable shoes
- Clevis hitch for easy hook-up
- Rugged laminated tailwheel
- Fully welded deck
- 3-Pt. with dual 15" tailwheels on 84"



5 YEAR
LIMITED GEARBOX
WARRANTY



3/16" Dishpan with 1" x 4" blade bar provides superior strength for encountering objects in the blade path. Round on 60" & 72"; oval on 84".

	RCR2660	RCR2672	RCR2684
Horsepower	35-130 HP		60-130 HP
Hitch	Cat. 1 & 2		Cat. 2 & 3
Working Width (cm)	60" (154)	72" (183)	84" (213)
Overall Width	67"	79"	90-3/4"
Overall Length	114"	126"	Single 133", Dual 116"
Weight - lb (kg)	1,002 (454)	1,046 (474)	1,370 (621) Single Gauge Wheel, 1,500 (680) Dual Gauge Wheel
Deck Thickness	10 Gauge		
Cutting Height	2"-12"		
Cutting Capacity	3" Diameter		
Safety Guards	Front: Chain; Rear: Single or Double Chain		
Skids	Full Length Weld & Replaceable Shoes		
Deck Height	9-1/8"	10-1/8"	
Blades	1/2" x 4" Heat Treated Alloy Steel Free Swinging Blades		
Blade Tip Speed	12,384 fpm	14,861 fpm	14,369 fpm
Dishpan	3/16" x 24" Round, Dish Shaped	3/16" x 30-1/2" Round, Dish Shaped	3/16" x 24" x 38" Oval, Dish Shaped
Gearbox Rating[^]	130 HP		
Gearbox	540 RPM PTO Driven, 1-3/8" 6 Spline Cast Iron Housing		
Driveline	Cat. 4 4-Plate Slip Clutch		
Tailwheel	4" x 8" x 15" Laminated Tire Cast Iron Hub		
Colors			

QuickHitch
SYSTEM