

RCFM4014 Model

Features	Benefits
Surpassed rugged industry standards	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures.
High gearbox horsepower rating	Gearboxes are built rugged. See Specifications for actual Gearbox horsepower ratings.
5 Yr. limited gearbox warranty	Shows our confidence in the gearbox integrity.
3 Gearboxes	Allows equal torque to be spread to left and right gearbox.
Splined blade hubs	Splined blade hub offers tight non-slipping attachment to gearbox output shafts.
High blade tip speed	Means cleaner cutting. See Specifications for actual blade tip speeds.
Spring loaded torque dampeners between center and outboard gearboxes	Protects the driveline and gearboxes from hard objects in the blade path and resets to prevent blades from hitting.
Slip-clutch protection on main driveline	Slip-clutch is more convenient than shear-bolt, protects gearbox against sudden impact.
Cat. 2 and Cat. 3 hitch	Fits a wide range of tractors.
10 Gauge (deck, fully welded	Fully welded deck adds rigidity.
1/4" (6 mm) Thick sidewalls	Protects sidewalls from thrown objects.
Round back design	Allows for cleaner and efficient discharge of material, helps eliminate damage to rear corners by not sticking out.
Full length skids with reversible & replaceable shoes	Adds reinforcement to side panels. Reversible and replaceable skid shoes allow for change before wearing through to weld-on piece.
Laminated tires	Laminated tires can handle almost any condition and don't go flat.
Dishpan option	Stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft. Heavy-duty blade bar adds support to stump jumper as well as gearbox output shaft.
Heat-treated blades 1/2" x 4" (13 mm x 10.2 cm)	Heat-treated blades last longer than non-heat-treated blades
3" (7.6 cm) Diameter cutting capacity	Aids in cutting brush.
Shredder kit options <p style="text-align: center;">Without fixed blades</p> <p style="text-align: center;">With fixed blades</p>	Good for Shredding row crops into small pieces. All kits include baffles to help maintain shredded material in each section of the cutter for a consistent rear discharge. Good for any row width. Good for 30" (0.76 m), 38" (0.97 m), and 40" (1.02 M) row spacings. Includes fixed blades to reduce stalks into smaller pieces.
Front rubber or chain guard options and rear metal band, rubber, or chain guard options	Reduces flying debris.
Three tailwheel option	Third tailwheel helps protect against scalping the ground on uneven terrain.