SC7072

| Features | Benefits |
|-------------------------------------|--|
| Case drain (optional) | Protects hydraulic motor and seals. |
| Front and rear chain guards | Chain guards on the front and rear of deck. Reduces flying debris. |
| Replaceable skid shoes | Protect side plate structure. Shoes are replaceable for convenience. |
| 3/4" x 7-1/2" free-swinging blades | Free-swinging blades protect from obstructions. |
| 7" cutting capacity | Easily cuts brushy areas & trees up to 7" in diameter. |
| Carbide teeth (standard) | Grind down tree stumps. |
| Push Bar | Pushes cut trees away from the operator cab. |
| Motor pressure gauge (optional) | Allows the operator to slow down to prevent stalling. |
| Bi-Folding door | Door will fold open when cutting heavy brush and trees. Covers the cutting chamber when not cutting in heavy brush. |
| Height adjustment safety chain | Provides additional operator protection from flying objects by allowing the Skid Cutter to only be lifted up to 18". |
| 1/4" thick deck | Heavy deck design holds up to harsh conditions. |
| Heavy blade carrier | Provides inertia & strength for cutting trees and grinding stumps. |
| Surpassed rugged industry standards | All Kubota Cutters have been designed and tested to meet rigorous voluntary testing procedures according to ISO 4254-13. |
| Polycarbonate door (optional) | Provides layer of protection between the cutter and operator. |
| 1/4" side panels | Reduces debris piercing possibilities. Can be replaced if damaged. |
| Beveled skid shoes on wings | Reduces gouging the ground when turning. |