

# RC3715 15' FOLDING ROTARY CUTTERS

HP REQUIRED  
50-160 HP

CUTTING CAPACITY  
3"

HITCH  
Pull-Type

CUTTERS



RC3715 HEAVY-DUTY		
Horsepower		50-160 HP
Hitch		Pull-Type; Standard Swivel Clevis, LP Performance Self-Leveling, Ball, Pintle, or Bar-Tite Hitch
Working Width (cm)		15' (457)
Overall Width		15'10"
Min. Transport Width		10'3"; 7'3" w/Narrow Option
Overall Length		16'3"
Machine Weight - lb (kg)		4,380 (1,987)
Cutting Height		1-1/2" - 16" **
Cutting Capacity		3" Diameter
Tongue Weight - lb		1,594
Max. Turning Angle		80° with CV
Deck Height		12"
Deck Thickness		10 Gauge
Suspension		Spring Cushioned Center Axle
Deck Rings		Optional
Side Panel Thickness		1/4"
Chain Guards Front & Rear		Single - Standard Double - Optional
Skid Shoes		Wings & Center, Replaceable, Beveled
Blades		1/2" x 4" Uplift
Blade Bolt		Keyed with Hardened Flatwasher & Lock Nut
Blade Tip Speed (Feet per minute)	540 Center	15,268 fpm
	Wings	15,000 fpm
	1000 Center	15,768 fpm
	Wings	14,620 fpm
Blade Overlap		6"
Hydraulics	Dishpan	3/16" Round, Dish Shaped, w/1" x 4" Blade Bar
	Wings	2-1/2" x 12"
	Center	3" x 8"
Gearbox Rating^		540 or 1000 RPM; 160 HP Divider; 130 HP Center & Wings
Gearbox Output Shaft		2"
Gearbox Input Shaft		1-3/4" 20 Spline
Input Driveline		Cat. 6 CV
Connecting Drivelines		Cat. 4 Slip Clutch
Tires		21" or 26" Laminated, 29" Used Aircraft, 25.5" Aircraft, or 24" Foam-Filled
Transport Lights		Standard
Color Options		<div><div></div><div></div><div></div><div></div><div></div></div>

## Tame the Plains.

The RC3715 is identical to the RC3712, simply 3 feet wider. It features a 3" cutting capacity, 12" deep deck, 1/4" side skirts, and is available in 540 or 1000 RPM. The tire offering on the RC3715 is expanded to 4, 6, or 8 tires in 4 sizes, including our new 26" laminated tire. Height adjustment utilizes flip over spacers as opposed to the donuts commonly used by competitors. The blades are 1/2" x 4" with a 6" overlap.



**5 YEAR**  
LIMITED GEARBOX  
WARRANTY



Fold options allow for narrow transport or independent control of the wings.



Sliding center shield offers ease-of maintenance for slip-clutches and U-joints.



Optional deck rings keep blades from damaging the cutter deck.